



VIVAX
METROTECH

VM-560 Service Drop Locator Kit

Technical Specifications V1.5



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-734-1415

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.ca

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road,
Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.co.uk

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
96110 Schesslitz

Tel : +49 9542 77227-43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

China

Vivax-Metrotech (Shanghai) Ltd.

Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980

Website : www.vivax-metrotech.com

Email : SalesCN@vxmt.com.cn

A. Description and Typical Applications

Item	Parameter	
Model Number	VM-560 Receiver	VM-560 Transmitter
	VX215-03	VX215-04
Description	VM-560 Three frequency Locator Kit	
Uses	General-purpose locators used to detect buried pipe and cable services	

B. Receiver Characteristics

Item	Parameter	
Construction	- High-impact ABS plastic housing with a carbon fiber reinforced antenna tube.	
Weight	1.41lbs (0.64kg)	
Dimensions	34.6in(L) x 3.1in(W) x 2.8in(H) (880mm x 80mm x 70mm)	
Display Type	Dot Matrix, 98 x 64 dots, COG LCD with backlight	
Controls	Four-button keypad	
Power Options	2 x AA Alkaline batteries	
Battery Life	Typically 20 hours of continuous use at 70°F (21°C)	
Environmental	IP54	
External Connectors	1 x Mini USB socket for programming	
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)	
Compliance and Approvals	- Complies with European standard CE (Directive 99/5/EC) • EN 55011 • EN 61000-4-2 • EN 61000-4-3 • EN 61000-4-8	- Complies with FCC Rules Part 15 • CFR 47 Part 15: 2006
Manufacturing	Designed and manufactured per ISO 9001:2015	
What's In the Box	- VM-550 Receiver - Battery holder - Kit carry bag	- Mini USB lead - Manual

C. Receiver Operational

Item	Parameter
Information Displayed	- Signal level - Battery condition - Power signal warning - Mode selected
Operating Frequencies	Passive: 50Hz, 60Hz Active: 512Hz or 640Hz, 8.192kHz, and 480kHz
Operating Modes	Passive Power and active locate modes
Gain / Scaling Control	Manual gain using "+" or "-" with one touch to return to center (60% of FSD)
Sensitivity	Frequency: 50/60Hz 5mA for 20dB SNR and 10Hz bandwidth 512/640Hz 1.5mA for 20dB SNR and 10Hz bandwidth 8.192kHz 27uA for 20dB SNR and 10Hz bandwidth 480kHz 6uA for 20dB SNR and 10Hz bandwidth
Accuracy	Depth range 5m (16ft), accuracy +/-5% of depth (with a stable signal)
Compatible Transmitters	VM-560FF, all Loc series transmitters with a matching frequency range

D. Transmitter Characteristics

Item	Parameter
Construction	High-impact ABS plastic
Weight	- With Alkaline battery tray: 2.47 lbs. (1.12kg) - With Rechargeable battery tray: 2 lbs. (0.92kg.)
Dimensions	18.1in(L) x 3.5in(W) x 2.6in(H) (460mm x 90mm x 65mm)
Display	Flashing red LED lights show active transmit and output modes.
Power Options	4 x Alkaline "D" cells Optional Li-Ion rechargeable battery pack
Battery Life	At 1 watt, i.e., full output setting. - Alkaline – typically 12 hours - Li-ion – typically 36 hours - Based on the maximum output into 300-ohm load and 50% duty cycle. At 70°F 21°C
Environmental	IP54 and NEMA 4

External Connectors	1 x 3-pin XLR socket	
Temperature Range	- Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C)	
Compliance/Approvals	- Complies with European standard CE (Directive 99/5/EC) • EN 55011 • EN 61000-4-3 • EN 61000-4-2 • EN 61000-4-4 • EN 61000-4-5 • EN 61000-4-8	- Complies with FCC rules part 15 • CFR 47 part 15
Manufacturing	Designed and manufactured per ISO 9001:2015	
What's In the Box	- Direct Connection Leads (XLR plug with 10-foot (3.5m) red/black leads) - Ground stake	- Carry strap
Compatible Accessories Options	- 2-inch (50mm) transmitter clamp - 4-inch (100mm) transmitter clamp - 5-inch (125mm) transmitter clamp - 9-inch (230mm) transmitter clamp - 18-inch (450mm) flexible transmitter clamp - Ground Extension Spool - Live Plug Connector (LPC Separation Filter) - to connect and use the transmitter on lines carrying up to 240V AC - LCC Live Cable Connector - to connect and use the transmitter on lines carrying up to 480V AC - Rechargeable Battery Pack - custom Li-Ion battery pack and charger - 12V DC Vehicle Power Lead - for powering and charging the optional rechargeable battery from a vehicle	

E. Transmitter Operational

Item	Parameter
Information Displayed	Solid and blinking LED shows - Frequency selected - Output power level
Transmitting Modes	- Induction mode – applies signal inductively using the internal antenna - Direct connection mode - applies signal directly to the cable by clipping one output lead to the cable, the other to an independent ground - Clamp mode – applies signal using an inductive clamp (aka toroid or coupler) that is placed around the target pipe or cable * Modes are automatically selected when accessories are plugged in. The default mode (no accessories) is Induction.

Transmitting Frequency by Mode

Induction Mode	480kHz
Direct Connection Mode	512Hz or 640Hz, 8.192kHz, and 480kHz
Clamp Mode	8.192kHz, and 480kHz
Fault Find Mode	8kFF, Fault locating mode for use with vLoc accessory A-frame or VM-510FFL ground fault locator (8.192kHz amplitude modulated with 8Hz and phase-modulated with 2.66Hz)
Transmitting Mode Power Output	- Per FCC part 15: • 1 watt – in High output level • 0.1 watt – in Low output level
Maximum Output Voltage	60V RMS
Maximum Output Current	Maximum output current = 70mA RMS constant current
Output Protection	Output protected against accidental connection to up to 240V AC
Audio Indication	- Connection quality – variable beep rate sound showing the better signal applied - Beep constantly – for high voltage detected
Controls	Use pushbuttons to select: - Power button: On / Off (Press and hold) - Low / High output (Short press) - Frequency
Compatible Receivers	VM-550, VM-560, VM-585, VM-510FFL+, vLoc3-Cam

F. Rechargeable Battery Tray (optional accessory)

Item	Parameter
Description	- Custom Lithium-Ion battery pack and charger - Li-Ion batteries will withstand 500 charging life cycles
Input/output	- Input: 8.4V ~ 8.5V - Output: 6V~8.4V
Battery Type	Li-Ion battery
Temperature Range	- Operating: 14°F to 140°F (-10°C to 60°C) - Storage : 14°F to 113°F (-10°C to 45°C)
Storage humidity	≤ 75% RH

Weight	1.26lb (0.57kg)
Dimension	8.3in(L) x 3.7in(W) x 2.5in(H) (210mm x 93mm x 63mm)
Shipping Weight	1.38lb (0.63kg)
Shipping Dimension	9in(L) x 3.7in(W) x 2.8in(H) (228mm x 95mm x 70mm)
Warranty	One Year

G. Kit Shipping and Packaging

Item	Parameter
Shipping Weight	- With alkaline batteries: 10.8lbs (4.9kg) - With Li-Ion batteries: 10.4lbs (4.7kg)
Shipping Dimension	39in(L) x 7.7in(W) x 4.7in(H) (990mm x 195mm x 120mm) (estimation)

H. Warranty

Item	Parameter
Warranty	- One Year - Extended warranty available

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.