



VIVAX
METROTECH

Loc3-25Tx, 25-Watt Transmitter

Technical Specifications V1.5



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-904-4964

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1- 408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.ca

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.co.uk

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
96110 Schesslitz

Tel : +49 9542 77227-42

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

China

Vivax-Metrotech (Shanghai) Ltd.

Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980

Website : www.vivax-metrotech.com

Email : SalesCN@vxmt.com.cn

A. Description and Typical Applications

Item	Parameter
Model Name	Loc3-25Tx
Model Number	VX222-02
Description	25-Watt Low-Frequency transmitter for buried utility locating and pipeline defect mapping
Designed Use	- Transmitting active signals for long-distance pipeline location - Transmitting active signals for the location of buried pipes and cables - Transmitting active signals for the location of coating defects on buried pipes

B. Characteristics

Item	Parameter									
Construction	High-impact ABS plastic									
Weight	7.05lbs (3.19kg)									
Dimension	13.1in(L) x 7.2in(W) x7.3in(H) (332mm x 182mm x 185mm)									
Display Type	- Monochrome-dot-matrix graphic LCD with LED backlight - 2.4in x 1.3in (60mm x 32mm)									
Power Supply	- Li-Ion rechargeable battery tray with AC to DC adapter (Optional 12 x D Cell Alkaline battery tray (output limited to 10W))									
Battery Life	<table><tr><th>Output Power</th><th>Alkaline</th><th>Li-Ion (Rechargeable)</th></tr><tr><td>25-watt</td><td>N/A</td><td>4 hours</td></tr><tr><td>*10-watt</td><td>4 hours</td><td>6 hours</td></tr></table> *When using Alkaline batteries, the output is limited to 10 watts *Continuous use at 70°F (21°C) with the backlight activated. The battery life varies with temperature, battery type and quality. Recharging cycles are approximately 500 times the life cycle. Based on the maximum output into a 50-ohm load and 50% duty cycle.	Output Power	Alkaline	Li-Ion (Rechargeable)	25-watt	N/A	4 hours	*10-watt	4 hours	6 hours
Output Power	Alkaline	Li-Ion (Rechargeable)								
25-watt	N/A	4 hours								
*10-watt	4 hours	6 hours								
Environmental	IP54									
External Connectors	- 1 x speakON® socket for clamps and connection leads - 1 x Mini-USB socket for firmware updates - 1 x socket for battery charger & 12V DC power in - 1 x fuse socket (output protection) with 1.6A/250V fuse									
Temperature Range	- Operating:-4°F to 122°F (-20°C to 50°C) - Storage:-40°F to 140°F (-40°C to 60°C)									

Compliance/Approvals	- Complies with European standard CE (Directive 99/5/EC) (Pending) • EN 55011 • EN 61000-4-3 • EN 61000-4-2: A1 & A2 • EN 61000-4-8: A1 • ETSI EN 300 330-2 • ETSI EN 301 489-1 • ETSI EN 301 489-3 - Complies with FCC Rules Part 15 (Pending) • CFR 47 part 2 • CFR 47 Part 15	
Manufacturing	Designed and manufactured per ISO 9001:2015	
What's In the Box	- Loc3-25Tx Transmitter - Ground stake - Transmitter carry bag - DC/AC Power supply for rechargeable battery - Direct Connection Leads (10ft (3.5m) red/black leads)	
Compatible Accessories Options	- 2-inch (50mm) transmitter clamp - 4-inch (100mm) transmitter clamp - 5-inch (125mm) transmitter clamp - 9-inch (230mm) transmitter clamp - 18-inch (450mm) flexible transmitter clamp - Ground Extension Spool - Backpack - Carry Bag - Connection leads with Telco or heavy-duty clips - Live Plug Connector (<i>LPC Separation Filter</i>) - to connect and use the transmitter on lines carrying up to 240V AC - LCC Live Cable Connector - to connect and use the transmitter on lines carrying up to 480V AC - Alkaline battery tray for 12 x D Cell (output limited to 10W) - 12V DC Vehicle Power Lead - for powering and charging the optional rechargeable battery from a vehicle - Adapter, 3-Pin XLR to speakON® for clamps and connection leads	

C. Operational

Item	Parameter
Information Displayed	- Current (numeric) - Volts - Resistance - Frequency of output signal - Beeper volume (three levels & off) - Battery condition icon - Output Step bar graph showing the proportion of signal current successfully applied - High voltage warning if utility-to-ground potential exceeds 21V (DC or AC peak) - Animation icon confirming connection mode (Direct connection or Clamp)
Transmitting Modes	- Direct connection mode applies a signal directly to the cable by clipping one output lead to the cable and the other to an independent ground. - Clamp mode – applies a signal using an inductive clamp (aka toroid or coupler) placed around the target pipe or cable. *Compatible frequencies of 8kHz and above. - *Modes are automatically selected when an accessory is plugged in.

Transmitting Frequency by Mode

Direct Connection Mode	- 3Hz/98Hz - 3Hz/128Hz - 4Hz/98Hz - 4Hz/128Hz; - ELF1-3Hz/6Hz/98Hz;	- ELF2-3Hz/6Hz/128Hz; - ELF3-4Hz/8Hz/98Hz; - ELF4-4Hz/8Hz/128Hz; - 3Hz/6Hz/512Hz;	- 3Hz/6Hz/640Hz; - 4Hz/8Hz/512Hz; - 4Hz/8Hz/640Hz - 20Hz to 9.82kHz
Clamp Mode	8kHz to 9.82kHz		
Transmitting Mode	In accordance with FCC part 15:		
Power Output	- Frequencies under 45 kHz - 25 watts - 25 watts Li-Ion rechargeable battery or external 19V 180W power adapter: - 10 watts when using alkaline batteries		
Maximum Output Voltage	- Li-Ion rechargeable battery, or external 19V 180W power adapter: 130V peak - 12V power adapter: 42V peak		
Maximum Output Current	- 1 Amp RMS constant output (<i>4 Amps Peak</i>) *Dependent on frequency and mode		
Output Protection	- Maximum utility-to-ground potential (operating): 21V (DC or AC peak) - Output protected against accidental momentary connection to up to 230V AC (rms)		
Audio Indication	- Connection quality – Increased beep rate indicates a better-applied signal - Beep to confirm the action		
Controls	- Use pushbuttons to select: • On/Off • Frequency • Output level Information (volts & resistance) / Setting (volume, frequency & multi-mode)		
Compatible Receivers	vLoc3 series		

D. Rechargeable Battery Tray

Item	Parameter
Description	Li-Ion rechargeable battery tray with charger
Input/output	- Input DC12V 3A - Output DC18V-93.6 Wh
Battery Type	Li-Ion battery

Temperature Range	- Operating: 14°F to 122°F (-10°C to 50°C) - Charging: 32°F to 113°F (0 °C to 45 °C) - Storage: -4°F to 140°F (-20°C to 60°C)
Storage humidity	≤ 75% RH
Weight	Battery Tray: 3.31lbs. (1.5kg)
Dimension	13.1in(L) x 7.2in(W) x 2.9in(H) (332mm x 182mm x 73mm)
Shipping Weight	4.6lbs (2.1kg) (Battery Tray)
Shipping Dimension	16.1in(L) x 10.2in(W) x 6.7in(H) (410mm x 260mm x 170mm)
Warranty	12 months

E. Shipping and Packaging

Item	Parameter
Shipping Weight	14.4lbs. (6.5kg)
Shipping Dimensions	15.7in(L) x 11.8in(W) x 8.7in(H) (400mm x 300mm x 220mm)

F. Warranty

Item	Parameter
Warranty	- 12 months - Extended warranty available

SpeakON® is a registered trademark of NEUTRIK AG.

Disclaimer: Product and accessory specifications and availability information are subject to change without prior notice.

Performance Disclaimer Actual performance may vary depending on environmental conditions, user technique, and signal interference.
Software & Firmware Disclaimer Functionality described may depend on the software or firmware version installed. Features are subject to modification through future updates.

Battery & Power Disclaimer Battery life is estimated and may vary based on settings, usage, temperature, and battery age.

Calibration Disclaimer Self-Test results confirm system consistency with factory calibration but do not replace periodic professional calibration if required by company policy or regulation.

Compliance Disclaimer Compliance with regional standards may vary by country. Users are responsible for ensuring the product is used in accordance with local laws and regulations.

Use Case Disclaimer The system is intended for professional utility locating and should not be used for purposes outside the manufacturer's defined scope.

Third-Party Services Disclaimer Use of GNSS correction services or cloud platforms may require third-party subscriptions and are subject to their terms and availability.

Feature Availability Disclaimer: Certain features, frequencies, or accessories may only be available in specific markets due to regional regulations or product certifications. Please consult your local Vivax-Metrotech representative for availability in your area.

Trademark Disclaimer: All product names, logos, and brands mentioned are the property of their respective owners. All company, product, and service names used in this document are for identification purposes only. Use of these names, logos, or brands does not imply endorsement.