

vCam Comparison Chart

Category	Control Module		vCam-6		vCamMX-2+		vCamDrain		vCam Wi-Fi Adapter	
Power			Internal Li-Ion Batteries		Internal Li-Ion Batteries		Internal Li-Ion Batteries		Internal Li-Ion Batteries	
Records to			1TB HDD, USB or SD		USB or VMC App		VMC App and USB		VMC App and USB	
App support (Wi-Fi)			Yes		Yes		Yes		N/A	
Display			9.7" / 24cm Daylight viewable HD (1024x 768)		8" / 20cm Daylight viewable TFT LCD (800x600)		N/A		Yes	
Controls			Pushbutton		Pushbutton		Touch icons in VMC App		Touch icons in VMC App	
Text writer			Full QWERTY keyboard		Onscreen keyboard or VMC App		Via VMC App		Via VMC App	
Audio commenting			Yes, internal microphone		Yes, internal microphone		Via VMC App		Via VMC App	
Category	Reels Type		Type-CP Reel	Type-MX Reel	150' MX Reel	100' MX Reel	70' Drain Reel	100' Drain Reel	Type-CP Reel	Type-MX Reel
Sonde			512Hz, 640Hz and 33kHz		512Hz, 640Hz and 33kHz		512Hz, 640Hz and 33kHz		512Hz, 640Hz and 33kHz	
Pushrod tracing			Yes		Yes		No		Yes	
Construction			Stainless-Steel	Stainless-steel & carbon fiber drum	Stainless-steel & carbon fiber drum		ABS Plastic		Stainless-Steel	Stainless-steel & carbon fiber drum
Compatible cameras			D34-HD, D46-HD	D18-HD, D26-HD	D18-HD, D26-HD		D18-HD, D26-HD		D34-HD, D46-HD	D18-HD, D26-HD
Applications			3 to 8 inches / 76 to 203mm Lateral and small diameter mains	2 to 4 inches / 50 to 101mm Lateral and roof vents	2 to 4 inches / 50 to 101mm Lateral and roof vents		2 to 4 inches / 50 to 101mm Residential and indoor plumbing		2 to 4 inches / 50 to 101mm Per attached reel	3 to 8 inches / 76 to 203mm Per attached reel